

# Preferred range of standard fabric types

Fabric Reference	Longitudinal Wires			Transverse Wires			Mass (kg/m <sup>2</sup> )
	Nominal wire size (mm)	Pitch (mm)	Area (mm <sup>2</sup> /m)	Nominal wire size (mm)	Pitch (mm)	Area (mm <sup>2</sup> /m)	
<b>Square Mesh</b>							
A393	10	200	393	10	200	393	6.16
A252	8	200	252	8	200	252	3.95
A193	7	200	193	7	200	193	3.02
A142	6	200	142	6	200	142	2.22
<b>Structural Mesh</b>							
B1131	12	100	1131	8	200	252	10.9
B785	10	100	785	8	200	252	8.14
B503	8	100	503	8	200	252	5.93
B385	7	100	385	7	200	193	4.53
B283	6	100	283	7	200	193	3.73
<b>Long Mesh</b>							
C785	10	100	785	6	400	70.8	6.72
C636	9	100	636	6	400	70.8	5.55
C503	8	100	503	6	400	49	4.51
C385	7	100	385	6	400	49	3.58
C283	6	100	283	6	400	49	2.78
<b>Wrapping Mesh</b>							
D98	5	200	98	5	200	98	1.54
D49	2.5	100	49	2.5	100	49	0.77
<b>Stock sheet</b>	Length 4.8m			Width 2.4m			Area 11.52 m <sup>2</sup>

**Table 1**